

MPPT Solar Charge Controller

Adopting Advanced MPPT Technology
High Conversion Efficiency



12V/24V/48V system auto recognition

Introduction:

This is a smart solar charge controller which has advanced MPPT technology .Solar charge controller is one of the important parts in the off-grid solar system. For having the advanced MPPT technology, the controller can trace the peak power with 99% conversion efficiency. MPPT microprocessor, inside the controller, making 30% more charge current with significantly less power than tradition. In addition to this, easier installing and supporting to expand volume are other advantages. It can also store energy to different kinds of batteries. We provide battery choice(Vented, Sealed, Gel, NiCd).

Feature:

1.MPPT charge mode,conversion efficiency up to 99%,can save 30%~60% of the power than traditional controller.

2.With high efficient MPPT operation scheme and adopting TI28035 chip,make the Solar panels utilization rate up to 99%.

Intelligent design,the device can be upgraded online,customers enjoy the lifelong upgrade service.

4.Compliance with the 2002/95/EC environment protecting demand, doesn't include the Cadmium, hydride and fluoride

5.Adopting the well-known brand components,the devices can suffer the temperature not less than 105°C.The service life is designed to extend to 10 years in theory.

6.Charge mode: three stages (fast charge,constant charge,floating charge)

7.12V/24V/48V system auto recognize for easy control.

8.Nominal maximum solar input is DC 150V

9.Connected Battery Type choosing: Sealed lead acid, vented, Gel, NiCd battery. Other types of the batteries can also be defined.

10. LCD and LEDs show all kinds of parameter like products model, PV input voltage,battery voltage,charge current,charge power,work condition,and also can add customers'company name and website.

11. Communication Port.RS232 communication can provide communication protocol, This make the unified and integrated management more convenient to customers.

12. With providing a Microsoft by connecting with PC that can show the working state and all parameters in 7 languages.

13. Extensible LAN remote control.

14.Equipment integrity: controller+CD-ROM(microcomputer software) + communication

wire+Anderson terminals;

15.CE,ROHS,FCC,PSE certifications approved.The device also can support to pass the other certifications.

16. 2 years warranty. And 3~10 years extended warranty service also can be provided.

Parameter:

Model: MS-DC12V/24V/48V-series		MS94229040	MS94229050	MS94229060
Charge Mode	Maximum Power Point Tracking			
Method	3 stages: fast charge(MPPT),constant voltage,floating charge			
System Type	DC12V/24V/48V	Automatic recognition		
System Voltage	12V system	DC9V~DC15V		
	24V system	DC18V~DC30V		
	48Vsystem	DC36V~DC60V		
Soft Start Time	12V/24V/48Vsystem	≤10S		
Dynamic Response Recovery Time	12V/24V/48Vsystem	500us		
Conversion Efficiency	12V/24V/48Vsystem	≥96.5%,≤99%		
PV Modules Utilization Rate	12V/24V/48Vsystem	≥99%		
Input Characteristics				
MPPT Working Voltage and Range	12V system	DC18V~DC150V		
	24V system	DC34~DC150V		
	48V system	DC65~DC150V		
Low Voltage Input Protection Point	12V system	DC16V		
	24V system	DC30V		
	48V system	DC60V		
Low Voltage Input Recovery Point	12V system	DC22V		
	24V system	DC34V		
	48V system	DC65V		
Max DC Voltage	12V/24V/48V system	DC160V		
Input Overvoltage Protection Point	12V/24V/48V system	DC150		
Input Overvoltage Recovery Point	12V/24V/48V system	DC145V		
Max. PV Power	12V system	570W	700W	900W
	24V system	1130W	1400W	1700W
	48V system	2270W	2800W	3400W
Output Characteristics				

Selectable Battery Types (Default type is GEL battery)	12V/24V/48Vsystem	Sealed lead acid, vented, Gel, NiCd battery (Other types of the batteries also can be defined)		
Constant Voltage	12V/24V/48V system	Please check the charge voltage according to the battery type form.		
Floating Charge Voltage	12V/24V/48V system			
Over Charge Protection Voltage	12V system	14.6V		
	24V system	29.2V		
	48V system	58.4V		
Rated Output Current	12V/24V/48V system	40A	50A	60A
Current-limiting Protection	12V/24V/48V system	44A	55A	66A
Temperature Factor	12V/24V/48V system	$\pm 0.02\%/^{\circ}\text{C}$		
Temperature Compensation	12V/24V/48V system	14.2V-(The highest temperature-25 $^{\circ}\text{C}$)*0.3		
Output Ripples(peak)	12V/24V/48V system	200mV		
Output Voltage Stability Precision	12V/24V/48V system	$\leq \pm 1.5\%$		
Display				
LCD display	Input,output parameter and output power etc (check the LCD display instruction)			
LED display	3 LEDs indicates:Fault indicate light,charge indicate light,power source indicate light(check the LED instruction)			
Software Control through PC(communication port)	RS232 (matching) or LAN(optional)			
Protection				
Input Low Voltage Protection	Check the input characteristics			
Input Overvoltage Protection	Check the input characteristics			
Input Polarity Reversal Protection	yes			
Output Overvoltage Protection	Check the output characteristics			
Output Polarity Reversal Protection	yes			
Short-circuit Protection	Recover after eliminating the Short-circuit fault,no problem for long term Short-circuit			
Temperature Protection	95 $^{\circ}\text{C}$			
Temperature protection	Above 85 $^{\circ}\text{C}$,decrease the output power,decrease 3A per degree.			
Other Parameters				
Noise	$\leq 40\text{dB}$			
Thermal methods	Forced air cooling,fan speed rate regulated by temperature,when inner temperature is too low,fan ran slowly or stop;when controller stop working,fan also stop ran.			
Components	World brand raw materials. Compliance with EU			

	standards.All rated temperature of electrolytic capacitors not less than 105°C
Smell	No peculiar smell and toxic substances.
Environment Protection	Meet the 2002/95/EC,no cadmium hydride and fluoride
Physical	
Measurement DxWxH(mm)	270*185*90
N.G(kg)	3
G.N(kg)	3.6
Color	Blue/Green (optional)
Safety	CE,RoHS, PSE,FCC
EMC	EN61000
Type of Mechanical Protection	IP21
Environment	
Humidity	0~90%RH (no condense)
Altitude	0~3000m
Operating Temperature	-20°C ~ +40°C
Storage Temperature	-40°C ~ +75°C
Atmospheric Pressure	70~106kPa



The specification is only for reference. Subject to change without prior notice.

We provide OEM and ODM service.The 36V/72V/96V model also can be custom made for you.



Top



Input



Accessories

The Figures of the PC Firmware and Testing Software




Figure 1: PC Firmware




Figure: Testing Software

Others Details

Please check the design brief,technical documents,product manual etc .