

LED EMERGENCY EXIT LIGHTS

Lifespan:>50000Hours
Comply To:SAA/CE/ROHS/IEC/TUV/SS563/SS508



TECHNICAL DATA

Model No.	: EB99024920
Power Consumption	: 4W
Power Supply	: AC110V/AC220V;50HZ/60HZ
Lighting Resource	: LED
Standby Time	: >3Hours
Charing Time	: <16Hours
Battery Type	: High Temperature NI-MH
Battery Capacity	: 1500mAH
Safety Features	: Low Volt Cut-Off Preventing Battery Overdischarge
Material	Body : PC Diffuser : PE
Mounting	: Wall Or Ceiling
Cable Entry	: Ø21.00mm Hole
Size:	: 358*212*60mm
Weight	: 0.8kgs
Warranty	: 3Years(Battery 1 Year)

ORDERING GUIDE

(Please check with Sales Dept. if Customisation is Required)

Ordering No.	Diffuser	Ordering No.	Diffuser
EB99024920(M)		EB99024920(E)	
EB99024920(L/R)		EB99024920(E/L)	
EB99024920(U)		EB99024920(E/R)	
EB99024920(D)			

KEY FEATURES

- >Diffusers Changeable
- >Wall and Ceiling Mountable
- >Quick & easy to install and maintain
- >Low Power Consumption
- >Long life
- >3Years Warranty(Battery 1Year)

PACKAGE INFORMATION

Inner Box	: 400*240*88mm
Gross Weight	: 1.2Kgs
Carton Size	: 372*347*444
Qty./Carton	: 10pcs
20FCL	: 2700Pcs
Loading Qty. 40FCL	: 5500Pcs
40HQ	: 7500Pcs

Specifications Subject To Changes Without Prior Notice

1

SUNWIND LIGHTING COMPANY LTD.

7th Floor,Block H,Juyin Industrial Park,Ganli Road 1#,Buji,Shenzhen,China 518112

T: 0086 755 8661 0835

F: 0086 755 8661 0201

E: sales@sunwindled.com

W: www.sunwindled.com



SUNWIND