

## LED EMERGENCY EXIT LIGHTS

Lifespan:>50000Hours  
Comply To:SAA/CE/ROHS/IEC/TUV/SS563/SS508

### TECHNICAL DATA



Model No. : EB18927511  
Power Consumption : 5W  
Power Supply : AC110V/AC220V;50HZ/60HZ  
Lighting Resource : LED  
Standby Time : >3Hours  
Charing Time : <16Hours  
Battery Type : High Temperature Ni-Cd  
Battery Capacity : 1800mAH  
Safety Features : Low Volt Cut-Off Preventing  
: Battery Overdischarge Preventing  
Material Body : Aluminum  
Diffuser : PVC  
Mounting : Wall, Ceiling Or Suspending  
Outlet Cable : Hard wired(Live/Neutral/Earth Wires)  
Size: : 415\*232\*32mm  
Weight : 1.50kgs  
Warranty : 3Years(Battery 1 Year)

### ORDERING GUIDE

(Please check with Sales Dept. if Customisation is Required)

Ordering No.	Diffuser	Ordering No.	Diffuser
EB18927511(M)		EB18927511(E)	
EB18927511(L/R)		EB18927511(E/L)	
EB18927511(U)		EB18927511(E/R)	
EB18927511(D)			

### KEY FEATURES

- >Diffusers Changeable
- >Wall,Ceiling and Suspending Mountable
- >Quick & easy to install and maintain
- >Low Power Consumption
- >Long life
- >3Years Warranty(Battery 1Year)

### PACKAGE INFORMATION

Inner Box : 435\*255\*55mm  
Gross Weight : 1.8Kgs  
Carton Size : 450\*560\*570  
Qty./Carton : 10pcs  
20FCL : 10000Pcs  
Loading Qty. 40FCL : 20000Pcs  
40HQ : 22000Pcs

Specifications Subject To Changes Without Prior Notice

1

**SUNWIND LIGHTING COMPANY LTD.**

7th Floor,Block H,Juyin Industrial Park,Ganli Road 1#,Buji,Shenzhen,China 518112

T: 0086 755 8661 0835

F: 0086 755 8661 0201

E: [sales@sunwindled.com](mailto:sales@sunwindled.com)

W: [www.sunwindled.com](http://www.sunwindled.com)



**SUNWIND**