

LED EMERGENCY EXIT LIGHTS

**EB99024960
Surface Installation**



**EB99024960-R
Recessed Installation**



Lifespan:>50000Hours
Comply To:SAA/CE/ROHS/IEC/TUV/SS563/SS508

TECHNICAL DATA

Model No.	: EB99024960	EB99024960-R
Power Consumption	: 4W	
Power Supply	: AC110V/AC220V;50HZ/60HZ	
Lighting Resource	: LED	
Standby Time	: >3Hours	
Charging Time	: <16Hours	
Battery Type	: High Temperature NI-MH	
Battery Capacity	Ni-Mh : 1.2V/2000mAH	
	LiFePO4 : 3.2V/500mAH	
Safety Features	: Low Volt Cut-Off Preventing	
	: Battery Overdischarge Preventing	
Body	: PC	
Material Diffuser	: PE	
	Diffuser Hold : Milk PC-With Light output	
Mounting	: Wall Or Ceiling Surface	Recessed
Cable Entry	: Φ21.00mm Hole	
Size:	: 358*215*60mm	420*217*76mm
Weight	: 1kgs	1.2kgs
Warranty	: 3Years(Battery 1 Year)	

Pictograms

(Please check with Sales Dept. if Customisation is Required)

Ordering No.	Diffuser	Ordering No.	Diffuser
EB99024960(M)		EB99024960(E)	EXIT
EB99024960(R)		EB99024960(E/L)	←EXIT
EB99024960(U)		EB99024960(E/R)	EXIT▶
EB99024960(D)		EB99024960(L)	←EXIT▶

KEY FEATURES

- >Blade Exit Sign
- >Ni-Mh and LiFePO4 battery optional
- >Diffusers Changeable
- >Wall and Ceiling Mountable
- >Quick & easy to install and maintain
- >Low Power Consumption
- >Long life
- >3Years Warranty(Battery 1Year)

PACKAGE INFORMATION

Inner Box	: 400*240*88mm	450*260*95mm
Gross Weight	: 1.2Kgs	1.5kgs
Carton Size	: 372*347*444	550*460*490
Qty./Carton	:	10pcs
20FCL	: 2700Pcs	2500pcs
Loading Qty. 40FCL	: 5500Pcs	5300pcs
40HQ	: 7500Pcs	7300pcs

Specifications Subject To Changes Without Prior Notice

SHENZHEN SUNWIND LIGHTING COMPANY LIMITED

Block 2,182 Industrial Park,Shanglilang,Buji,Shenzhen,China 518112
T: +86 755 8661 0835 F: +86 755 8661 0201
E: sales@sunwindled.com W: www.sunwindled.com



SUNWIND