

LED EMERGENCY EXIT LIGHTS

Lifespan:>50000Hours
 Comply To:SAA/CE/ROHS/IEC/TUV/SS563/SS508

TECHNICAL DATA

Model No. : EB99024970
 Power Consumption : 4W
 Power Supply : AC110V/AC220V;50HZ/60HZ
 Lighting Resource : LED
 Standby Time : >3Hours
 Charging Time : <16Hours
 Battery Type : High Temperature NI-MH
 Battery Capacity : Ni-Mh : 1.2V/2000mAH
 LiFePO4 : 3.2V/500mAH
 Safety Features : Low Volt Cut-Off Preventing
 Battery Overdischarge Preventing
 Body : PC
 Material Diffuser : PE
 Diffuser Hold : Milk PC-With Light output
 Mounting : Wall Or Ceiling Surface
 Cable Entry : Ø21.00mm Hole
 Size: : 358*215*60mm
 Weight : 0.8kgs
 Warranty : 3Years(Battery 1 Year)

Pictograms

(Please check with Sales Dept. if Customisation is Required)

Ordering No.	Diffuser	Ordering No.	Diffuser
EB99024970(M)		EB99024970(E)	
EB99024970(R)		EB99024970(E/L)	
EB99024970(U)		EB99024970(E/R)	
EB99024970(D)		EB99024970(L)	

KEY FEATURES

>Milk Diffuser holder(light output on the sides and bottom)
 >Ni-Mh and LiFePO4 battery optional
 >Diffusers Changeable
 >Wall and Ceiling Mountable
 >Quick & easy to install and maintain
 >Low Power Consumption
 >Long life
 >3Years Warranty(Battery 1Year)

PACKAGE INFORMATION

Inner Box : 400*240*88mm
 Gross Weight : 1.2Kgs
 Carton Size : 372*347*444
 Qty./Carton : 10pcs
 20FCL : 2700Pcs
 Loading Qty. 40FCL : 5500Pcs
 40HQ : 7500Pcs

Specifications Subject To Changes Without Prior Notice

SHENZHEN SUNWIND LIGHTING COMPANY LIMITED

Block 2,182 Industrial Park,Shanglilang,Buji,Shenzhen,China 518112

T: +86 755 8661 0835

F: +86 755 8661 0201

E: sales@sunwindled.com

W: www.sunwindled.com



SUNWIND