

LED EMERGENCY LIGHT-AUSTRALIA&NEW ZEALAND-SAA/AS2203.3 STANDARD

LiFePO4



Mounting	Surface
Model No.:	EB99024920
Capacity:	4W
Dimension(mm):	360*210*62
Viewing Distance:	24M
Input Voltage:	AC240V/50Hz
Battery:	LiFePO4
Installation:	Wall/Ceiling
Charging Time:	<16Hours
Standby Time:	>3Hours

LiFePO4



Mounting	Surface
Model No.:	EB99024970
Capacity:	4W
Dimension(mm):	358*215*60
Viewing Distance:	24M
Input Voltage:	AC240V/50Hz
Battery:	LiFePO4
Installation:	Wall/Ceiling
Charging Time:	<16Hours
Standby Time:	>3Hours

LiFePO4



Mounting	Surface
Model No.:	EB99024960
Capacity:	4W
Dimension(mm):	358*215*60
Viewing Distance:	24M
Input Voltage:	AC240V/50Hz
Battery:	LiFePO4
Installation:	Wall/Ceiling
Charging Time:	<16Hours
Standby Time:	>3Hours

LiFePO4



Mounting	Recessed
Model No.:	EB99024960-R
Capacity:	4W
Dimension(mm):	420*217*76
Viewing Distance:	24M
Input Voltage:	AC240V/50Hz
Battery:	LiFePO4
Installation:	Wall/Ceiling
Charging Time:	<16Hours
Standby Time:	>3Hours



IP65



Item Name:	LED Exit Sign
Model No.:	EB18927511
Dimension(mm):	415*232*32
Capacity:	2W
Viewing Distance:	24M
Input Voltage:	AC240V/50Hz
Battery:	High-Temp Ni-Mh
Installation:	Wall/Ceiling
Charging Time:	<16Hours
Standby Time:	>2Hours

Mounting	Surface
Model No.:	EB99060965
Capacity:	4W
Dimension(mm):	381*162*98
Viewing Distance:	24M
Input Voltage:	AC240V/50Hz
Battery:	Li-Ion
Installation:	Wall/Ceiling
Charging Time:	<16Hours
Standby Time:	>3Hours



Item Name:	LED Spitfire-2W/5W
Model No.:	2W EL98947070
	5W EL98940505
Lumen	2W 130lm
Output:	5W 250lm
Input Voltage:	AC240V/50Hz
Battery:	High-Temp Ni-Cd
Installation:	Recessed
Charging Time:	<16Hours
Standby Time:	>2Hours



Item Name:	LED Spitfire-2W/5W
Model No.:	2W EL9997070
	5W EL98940505
Lumen	2W 130lm
Output:	5W 250lm
Input Voltage:	AC240V/50Hz
Battery:	High-Temp Ni-Cd
Installation:	Surface
Charging Time:	<16Hours
Standby Time:	>2Hours



Item Name:	LED Oyster Light
Model No.:	CL99108016
Dimension(mm):	Φ370*115
Capacity:	16W
Lumen Output:	1300lm
Input Voltage:	AC240V/50Hz
Battery:	High-Temp Ni-Cd
Installation:	Wall/Ceiling
Charging Time:	<16Hours
Standby Time:	>3Hours

Item Name:	IP65 LED Battens
Model No.:	ET96121036-IP65
Dimension(mm):	1270*151*95
Capacity:	36W
Lumen Output:	3600lm
Input Voltage:	AC240V/50Hz
Battery:	LiFePO4
Installation:	Surface/Suspend
Charging Time:	<16Hours
Standby Time:	>2Hours

Item Name:	LED Battens
Model No.:	ET98941636
Dimension(mm):	1250*120*92
Capacity:	36W
Lumen Output:	3600lm
Input Voltage:	AC240V/50Hz
Battery:	High-Temp Ni-Cd
Installation:	Surface
Charging Time:	<16Hours
Standby Time:	>2Hours

Item Name:	Emergency Kits
Model No.:	EP28000294
Capacity:	Max 18W
	LED Tube
Suitable for	LED Downlight
	LED Spotlight
Input Voltage:	AC240V/50Hz
Battery:	High-Temp Ni-Mh
Installation:	Wall/Ceiling
Charging Time:	<16Hours
Standby Time:	>2Hours

Specifications Subject To Changes Without Prior Notice

SHENZHEN SUNWIND LIGHTING COMPANY LIMITED

Block 2,182 Industrial Park,Shanqiliana,Buji,Shenzhen,China 518112

T: +86 755 8661 0835

F:

+86 755 8661 0201

E: sales@sunwindled.com

W:

www.sunwindled.com

